

Safety equipment

mandatory signs 10

N = 200 mm. M = 150 mm. Materials: PV, PR, V & R

 Wear helmet	 This is a safety helmet area	 Head protection must be worn	 Wear goggles	 Eye protection is provided for your safety and must be worn	 Eye protection must be worn in this area	 Eye protection must be worn	 Wear ear protection	 Ear protection must be worn in this area
106.038 NM	106.035 NM	106.022 C	106.040 NM	106.041 NM	106.036 NM	106.021 NM	106.045 NM	106.037 NM
 Ear protection required	 Boots must be worn	 Protective footwear must be worn	 Wear face shield	 Face protection must be worn in this area	 Wear respirator	 Additional breathing apparatus	 Wear non-skid footwear	 Antistatic footwear must be worn
106.023 NM	106.050 NM	106.029 NM	106.031 NM	106.055 NM	106.020 NM	106.032 NM	106.028 NM	106.027 NM
 Hand wash only	 Now wash your hands	 Wear mask	 Hair covering must be worn	 Hand protection must be worn	 Wear gloves	 Chemical suit	 Protective clothing must be worn in this area	 Wear safety harness
106.060 NM	106.061 NM	106.065 NM	106.066 NM	106.025 NM	106.067 NM	106.024 NM	106.068 NM	106.030 NM
 Think safety	 Keep clear	 Keep shut	 Secure painter to strong point before launching	 Adjust pressure according to the torch in use	 This door must be kept closed during loading, discharging, ballasting, tank cleaning and gas freeing operations	 When the plant is not in use gas cylinder valves and other valves shall be shut	 Ventilation to be used prior to entry	
106.034 NM	106.070 NM	106.071 NM	106.072 NM	106.073 NM	106.074 NM	106.075 NM	106.076 NM	106.077 NM
 Face protection must be worn when welding	 Guards must be in position before starting	 Lift correctly	 CO ₂ Protected area <small>On hearing alarm vacate space immediately. Close all exits behind you.</small>	 Start ventilation before entering	 Lifejackets must be worn at all times	Materials: PV = Photoluminescent vinyl PR = Photoluminescent plast V = Self adhesive vinyl R = Rigid plast Size Codes: M = 150 mm. N = 200 mm.		
106.080 NM	106.081 NM	106.082 NM	106.083 NM	106.033 NM	106.084 NM			

M = 150 mm. Materials: PV, PR, V & R

 Fire escape keep clear	 Gangway keep clear	 Fire door keep shut	 Keep locked shut when not in use	 Keep clear when door is closing	 This hatch must be kept closed at sea	 This door must be kept closed at sea	 Watertight door keep shut	 Automatic watertight door keep clear	 Ensure this door is fully closed
106.100 MM	106.101 MM	106.102 MM	106.103 MM	106.104 MM	106.105 MM	106.106 MM	106.107 MM	106.108 MM	106.109 MM
 Exit keep clear	 Fire exit keep clear	 Think safety	 This door to be kept locked when not in use	 This door must be kept closed	 Keep clear	 Fire notice This area must be kept clear at all times	 Close these doors at night	 To be kept unlocked during working hours	 Keep clear. Exit for emergency escape route
106.110 MM	106.111 MM	106.112 MM	106.113 MM	106.114 MM	106.115 MM	106.116 MM	106.117 MM	106.118 MM	106.119 MM
 Fire door keep locked shut	 Automatic fire door keep clear	 Staircase must be kept clear at all times	 Close this door at night						
106.120 MM	106.121 MM	106.122 MM	106.123 MM						
 106.150 MM	 106.151 MM	 106.152 MM	 106.153 MM	 106.154 MM	 106.155 MM	 106.156 MM	 106.157 MM	 106.158 MM	 106.159 MM
106.150 MM	106.151 MM	106.152 MM	106.153 MM	106.154 MM	106.155 MM	106.156 MM	106.157 MM	106.158 MM	106.159 MM
 106.160 MM	 106.161 MM	 106.162 MM	 106.163 MM	 106.164 MM	 106.165 MM	 106.166 MM	 106.167 MM	 106.168 MM	 106.169 MM
106.160 MM	106.161 MM	106.162 MM	106.163 MM	106.164 MM	106.165 MM	106.166 MM	106.167 MM	106.168 MM	106.169 MM