

Materials:

Photoluminescent Self Adhesive Vinyl (PV)

Flexible PVC foil with a photoluminescent layer.

Luminance: Min. 20/3,8 mcd/m² (after 10 and 60 min) DIN 67510 requires 20/2,8 mcd/m²

Thickness: approx. 0,35 mm

Weight: approx. 500 g/m²

Indoor durability: ~ 5 years

Outdoor durability: ~ 2 years (Can be reduced in strong sunlight)

Foil for marking of escape routes, places of danger, manufacturing of guidance lines, general marking, etc.

This material also comes with a luminance of 150/22 mcd/m²

Photoluminescent Rigid PVC (PR)

Luminance: Min. 20/3,8 mcd/m² (after 10 and 60 min) DIN 67510 requires 20/2,8 mcd/m²

Indoor durability: ~ 5 years

Outdoor durability: ~ 5 years (Can be reduced in strong sunlight)

Self Adhesive Vinyl (V)

Flexible Gloss white vinyl material.

Soft calendered PVC film. Cadmium free, gloss finish.

Adhesive: Permanent high-performance, acrylic water based.

Liner: Coated Kraft Paper, approx. 140 g/m²

Laminate: approx. 260 g/m²

Indoor durability: ~ 3 years

Outdoor durability ~ 2 years

Rigid Polystyrene (R)

Extruded high-impact polystyrene

Indoor durability: ~ 5 years

Outdoor durability ~ 2 years (Can be reduced in strong sunlight)

